




## PT 5504/L

(*)				
T	°C	-200 +280		
p	bar		100	25
V	m/s		2	8
pH		0 , 14		



(\*) Not use the product to the maximum temperature and pressure associated without to consult the manufacturer

### Composition

- continuous virgin PTFE yarn
- emulsion of PTFE and Silicon
- high thermal conductor coumpound

### Features

Innovative packing suitable for severe applications that improves the thermal conductivity features of pure PTFE.

Every yarn is lubricated with special coumpound in order to reduce glazing and to improve the resistance to the thermal expansion.

### Applications

Pumps, mixers and agitators applications in Paper Mills, Chemical Plants, Food and Pharmaceutical Industry

sezione mm	sezione inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	58,5	192	58,5	87,1
4,0	-	1,0	2,2	32,9	108	32,9	49,0
5,0	3/16	1,0	2,2	21,1	69	21,1	31,4
6,0	-	2,5	5,5	36,5	120	14,6	21,8
6,5	1/4	2,5	5,5	31,1	102	12,5	18,6
8,0	5/16	2,5	5,5	20,6	67	8,2	12,2
9,5	3/8	2,5	5,5	14,6	48	5,8	8,7
10,0	-	2,5	5,5	13,2	43	5,3	7,8
11,0	7/16	2,5	5,5	10,9	36	4,3	6,5
12,0	-	2,5	5,5	9,1	30	3,7	5,4
12,7	1/2	2,5	5,5	8,2	27	3,3	4,9
14,0	9/16	5,0	11,0	13,4	44	2,7	4,0
16,0	5/8	5,0	11,0	10,3	34	2,1	3,1
17,5	11/16	5,0	11,0	8,6	28	1,7	2,6
18,0	-	5,0	11,0	8,1	27	1,6	2,4
19,0	3/4	5,0	11,0	7,3	24	1,5	2,2
22,0	7/8	5,0	11,0	5,4	18	1,1	1,6
25,5	1	5,0	11,0	4,0	13	0,8	1,2
packaged +/- 10 % in weight							