

STYLE P20

**Highest purity carbon fibre impregnated
with special dynamic silicon free run-in lubricant**



p [bar]	30 (25*)	100	100
v [m/s]	25	2	-
t °C	-50 ... +300 (250*)		
pH	2 - 12		
g/cm ³	1.45		

*practically useful data

Main areas of application:

- Boiler feed water pumps
- Centrifugal pumps
- Blenders
- Agitators
- Kneading devices
- Refiners

Characteristics:

- Highest practical standardisation potential
- Wear resistant with abrasive media, nevertheless shaft protecting HRC45 shaft hardness recommended
- Thermally well-balanced structure, volume stable, insignificant shrinkage, excellent heat conductivity
- Outstanding chemical and physical characteristics
- Also recommended as end rings for softer packing as Style P60 and A44

Suitable for:

- Power plants, boiler houses, paper and pulp, chemical industries

Form of delivery:

This packing can be manufactured from 4 to 40 mm square as well as in intermediate, inch sizes and special measurements.

04 - 09 mm	on	1 kg spool	Special length, pre-cut or die formed rings on request.
10 - 15 mm	on	2.5 kg spool	
16 mm and above	on	5 kg spool	

1 kg of packing of the following cross-sections is equivalent to displayed metre lengths:

[size]	04	05	06	1/4"	08	3/8"	10	7/16"	12	1/2"	14	15	16	18	19	20	22	25
[m]	43.1	27.6	19.2	17.1	10.8	7.6	6.9	5.7	4.8	4.1	3.5	3.1	2.7	2.1	1.9	1.7	1.4	1.1

All technical information and advice is based on our experience and will be given most conscientiously but without any liability. Indication and figures need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.